

3A

3A40A (夾接頭用) 無蓋墊片	Clamp Ferrule Gasket UNFLANGED mm			
	SIZE	A	B	C
	1/2"	4.3	9.4	21.8
	3/4"	4.3	15.8	21.8
	7/8"	4.8	17.3	34
	1"	5.15	22.1	50.4
	1 1/4"	5.15	28.45	50.4
	1 1/2"	5.15	34.8	50.4
	2"	5.15	47.5	63.9
	2 1/2"	5.15	60.2	77.4
	3"	5.15	72.9	90.9
	3 1/2"	5.15	85.1	106.0
	4"	5.15	97.4	118.9
	4 1/2"	5.15	110.3	130
	6"	5.15	146.9	166.9
	8"	5.15	197.6	217.7
	10"	5.15	247.2	268.5
	12"	5.15	298.0	319.3

3A40B (夾接頭用) 有蓋墊片	Clamp Ferrule Gasket FLANGED mm			
	SIZE	A	B	C
	1"	5.15	22.1	50.4
	1 1/2"	5.15	34.8	50.4
	2"	5.15	47.5	63.9
	2 1/2"	5.15	60.2	77.4
	3"	5.15	72.9	90.9
	3 1/2"	5.15	85.1	106.0
	4"	5.15	97.4	118.9
	6"	5.15	146.9	166.88
	12"	5.15	298.0	319.3

DIN 11851

DIN40 DIN墊片	DIN GASKET (DIN 11851) mm			
	SIZE	A	B	C
	10	5.0	12.0	20.0
	15	5.0	18.0	26.0
	20	5.0	23.0	33.0
	25	5.0	30.0	40.0
	40	5.0	42.0	52.0
	50	5.0	54.0	64.0
	65	5.0	71.0	81.0
	80	5.0	85.0	95.0
	100	6.0	104.0	114.0
	125	6.0	130.0	142.0
	150	6.0	155.0	167.0



食品衛生級 配管用墊片

RJT/BSM/CIP Flat Face

RJT40A BSM墊片 (AUS)	BSM Gasket, AUS & UK market, not for Clean-In-Place mm			
	SIZE	A	B	
	1"	6.6	33.3	
	1 1/2"	6.6	46.0	
	2"	6.6	58.7	
	2 1/2"	6.6	71.4	
	3"	6.6	84.1	
	4"	6.6	109.5	
	6"	6.6	160.0	

IDF

IDF40 IDF墊片	IDF GASKET (IDF) mm				
	SIZE	A	B	C	D
	1"	7.0	23.0	29.0	32.0
	1 1/2"	7.0	35.7	42.5	46.0
	2"	7.0	47.8	56.0	59.0
	2 1/2"	7.0	59.5	69.0	72.5
	3"	7.0	72.3	82.0	86.0
	4"	7.0	97.6	108.5	114.0

SMS 1145

SMS40 SMS墊片	SMS GASKET (SMS 1145) mm			
	SIZE	A	B	C
	1" (25)	5.5	25.0	32.1
	1 1/2" (38)	5.5	38.0	48.1
	2" (51)	5.5	51.0	61.1
	2 1/2" (63)	5.5	63.5	73.6
	3" (76)	5.5	76.0	86.1
	4" for 104 & 101.6	5.5	104.0	116.2

RJT40B CIP墊片 (CIP FLAT FACE)	Gasket CIP FLAT FACE mm			
	SIZE	A	B	C
	1"	7.0	22.5	26.7
	1 1/2"	7.0	35.2	39.4
	2"	7.0	47.9	52.1
	2 1/2"	7.0	60.85	64.8
	3"	7.0	73.3	77.5
	4"	7.0	98.7	102.9
	6"	7.1	149	153.4

\*\*\* The Flat Face CIP(Clean-in-Place) seal fills the gap between the LINER and MALE

RJT40C RJT墊片 (NZ)	RJT Stepped Gasket for NZ market			
	SIZE	A	B	C
	1"	12.84	22.9	26.87
	1 1/2"	12.84	34.84	39.6
	2"	12.84	47.9	52.3
	2 1/2"	12.84	60.85	65.0
	3"	12.84	73.3	77.7
	4"	12.84	98.7	103.1
	6"	12.84	148.5	153.4

玄盛企業股份有限公司 食品衛生級 墊片材料特性 比較表  
" Gasket Material Selection Guide / Gasket Material Characteristics Comparison Chart " - TECH CONTROL ENTERPRISE CO., LTD.

墊片材料特性 Gasket Material Characteristics	SILICONE	EPDM	VITON (FKM)	TEFLON (PTFE)	BUNA-N
建議操作溫度 Recommend Operating Temperature	-30°C~120°C	-30°C~100°C	-15°C~120°C	-30°C~160°C	-10°C~100°C
耐酸鹼度 Acid/Alkali Resistance	一般 Fair	一般 Fair	良 Good	優 Excellent	一般 Fair
耐臭氧度 Ozone Resistance	一般 Fair	優 Excellent	一般 Fair	一般 Fair	差 Poor
顏色 Color	白色半透明 Translucent White	黑 Black	黑 Black	白 White	原色為淺褐色, 可訂製為白色 Original color is light brown, customizable to white
其它備註事項 Other Comments	耐高溫 heat resistant	耐臭氧 Ozone resistance	耐酒精 alcohol resistance	耐酸鹼及溶劑 acid, alkali, and solvent resistant, 硬 hard	耐油 oil resistance